



Direct Drilling

BDA accredited

160 Invicta Road
Sheerness
Kent ME12 2AG

Tel / Fax : (01795) 664283
Tel : (01795) 666221
Mobile : (0831) 239668

LANDFILL
SOAKAWAYS
SITE INVESTIGATION

Depth		Strata Description	Penetration Testing and Samples									
G/L			Type	From	To	75	150	225	300	375	450	Blows
		FIRM BROWN SANDY CLAY, WITH SCATTERED GRAVELS, AND FINE BRICK FRAGMENTS.										
1.30		WASTE, BRICK, PLASTIC AND ABUNDANT WOOD IN A BLACK ORGANIC CLAY MATRIX.										
10.20		STIFF, LIGHT REDDISH-BROWN SILTY-SANDY CLAY WITH SCATTERED MED SIZED GRAVELS AND FINE CHALK STONES.										
13.20		STIFF GRAY SILTY CLAY WITH FINE CHALK STONES.										
		DRIILLED TO 13.50										

Remarks INSTALLED 13.80 x 100mm LINER, DETAILS ON SEPARATE SHEET.

Driller
M. Y. Claxton

Water Levels					
Depth	Casing	Time			
Morning					
Evening					
Other					
Depth at end of day					
Diameter (mm)	Borehole	Casing			
200	13.50	10.50			
Hard Strata / Chiselling					
From (M)	To (M)	From (Hrs)	To (Hrs)		
Total number of samples					
SPT	B	U100	D	H ² O	P

H ² O	Strike 1	Strike 2	Strike 3	
Depth	6.80			
Depth 5 mins				
Depth 10 mins				
Depth 15 mins				
Depth 20 mins				
Casing				
Cut off at				
Move	Drill	Stand	Break	Work
1	13.50			4 hrs
Site				
COLE GREEN				
Job No.			B / H No.	V14
Day			Date	21-8-97
THURSDAY				